	Project Name: _		AIA#:
Model #:		Location:	



Globe 60 Quart Planetary Floor **Mixers**

The Perfect Mix of Value. Performance & Durability

This award-winning mixer features 3 fixed speeds and front-mounted touch pad controls with a digital timer.









Model

☐ SP60

Standard Features

- Powerful 3 HP custom built motor
- Gear-driven, high-torque transmission
- Heat-treated hardened steel alloy gears & shafts
- Three fixed speeds
- Permanently lubricated transmission
- Thermal overload protection
- Front-mounted touch pad controls with 60-minute digital timer and last-batch recall
- Removable stainless steel, interlocking bowl guard with built-in, fully welded ingredient chute
- Safety interlocked bowl lift
- Rigid cast iron body
- Industry standard #12 attachment hub
- NSF approved enamel gray paint
- 6-foot cord and ground plug

Standard Accessories/Attachments

- 60 gt stainless steel bowl (#304 series)
- Aluminum flat beater
- Stainless steel wire whip
- Aluminum spiral dough hook
- Non-slip rubber feet
- Bowl truck

Warranty


Two years parts and labor


Optional Accessories/Attachments

- Seismic flange kit
- Polycarbonate splash shield insert
- Slicer/shredder/grater for #12 hub
- Meat grinder for #12 hub
- Meat tenderizer for #12 hub
- Strip cutter for #12 hub
- Stainless steel flat beater
- Stainless steel whip
- Bowl scraper
- Additional bowl truck
- 30 qt. adapter kit
- 40 qt. adapter kit
- Extended warranty

To select options see back

Approved by:	Date:
" ,	





Drawings available through KCL at www.kclcad.com.

SPECIFICATIONS												
Model	Motor	Volts	Amps	Transmission Type	Capacity	Controls	Agitato 1st	r Speeds (I 2nd	RPMs) 3rd	Attachm 1st	ent Speeds 2nd	(RPMs) 3rd
SP60	3 HP	220/60/1* 208/60/3*	23 9	Gear	60 qt / 57 liter	Front-mounted digital controls & timer	73	120	267	49	82	181

Cord & Plug: Attached 6-foot flexible 3-wire cord with molded plug fits a grounded receptacle. Single phase NEMA L6-30P (1) Three phase NEMA L15-20P (1) *Specify voltage when ordering.

DIMENSIONS | SHIPPING INFORMATION

Reinforced carton for shipping. The weight and dimensions of this reinforced carton are included below and may vary from shipment to shipment. This product ships on a pallet, Freight class 85.

The product ships on a panet. Freight stass out							
Model	Overall Dimensions	Net Weight	Shipping Dimensions	Shipping Weight			
SP60	25.25" W x 30.5" D x 51.5" H (64 cm x 77 cm x 131 cm)	572 lbs (260 kg)	46" W x 48" D x 65" H (122 cm x 122 cm x 165 cm)	700 lbs (317.5 kg)			

Mixer is constructed of a rigid cast iron body with controls and 60-minute digital timer with last-batch recall. Mixer has 3 HP custom built motor with overload protection and gear-driven, high-torque, permanently lubricated transmission consisting of heat-treated hardened steel alloy gears and shafts. Mixer comes with 60 qt. stainless steel bowl, aluminum flat beater, stainless steel bowl truck and wire whip, aluminum dough hook and non-slip rubber feet. Interlocked with removable stainless steel bowl guard with fully welded ingredient chute. Mixer has #12 attachment hub and interlocked bowl lift. Mixer is NSF and ETL listed. Two-year parts and labor warranty.

OPTIONAL MIXER ACCESSORIES AND HUB ATTACHMENTS							
MIXER: XXSEISMIC KIT-MD Seismic kit XXBGSHIELD-60 Bowl guard shield XXBOWL-60 60 qt stainless steel bowl XXBEAT-60 Alum. flat beater	Node 9 Silicer/Silredder/Grater	 XGP* Grating plate *Only 1 plate holder required XMCA-SS Meat grinder assembly (Polished stainless steel cylinder, worm gear, ring, and s/s pan. Includes knife, 	CP18-12 11/16" (18 mm) CP00-12 Stuffing plate XST12 1/2" Stuffing tube (mutton) XST34 3/4" Stuffing tube (pork)				
XXBEAT-60SS S/S flat beater XXHOOK-60 Alum. dough hook XXWHIP-60 S/S wire whip XXHDWHIP60-4 Heavy-duty 4 mm S/S wire whip	housing only (no plates included-must select from plates listed on this sheet) XASP Adjustable slicing plate (veg. only) XPH Plate holder L00670 Meat Tenderizer attachment	3/16" plate, and pusher)	FACTORY INSTALLED OPTION: XXCORR-60 Correctional package, includes tamper resistant external fasteners. EXTENDED WARRANTY				
■ XXHDWHIP60-5 Heavy-duty 5 mm S/S wire whip ■ XXSCRP-60 scraper with mounting kit ■ XXACC30-60 Adapter kit - 30 qt bowl, hook, beater and whip ■ XXACC40-60 Adapter kit - 40 qt bowl, hook, beater and whip	☐ L00783 Strip Cutter attachment Shredding Plates: ☐ XSP332* 3/32" (2.3 mm) ☐ XSP316* 3/16" (4.7 mm) ☐ XSP14* 1/4" (6.3 mm) ☐ XSP516* 5/16" (7.9 mm) ☐ XSP12* 1/2" (12.7 mm)	CP05-12 3/16" (5 mm) CP06-12 1/4" (6 mm) CP08-12 5/16" (8 mm) CP10-12 3/8" (10 mm) CP12-12 1/2" (12 mm) CP14-12 9/16" (14 mm) CP16-12 5/8" (16 mm)	SP-XD4060 Extended warranty for SP60 mixer, extends factory warranty to 3 years. Available only at time of purchase.				